

MULTI CORE FLEXIBLE PVC INSULATED PVC SHEATHED CABLE (H05V2V2-F_105 DEG C) AS PER GENERALLY TO BS EN 50525-2-11

APPLICATION

This type of cable is designed to withstand medium mechanical stresses and allows for frequent bending and twisting. It is particularly well-suited for use in household environments, kitchens and offices, including applications with washing machines, dryers and refrigerators, provided it meets the device's specifications. It is also suitable for fixed installation within furniture, partition walls, decorative linings and cavities in prefabricated construction elements, even in dry and damp conditions.

CONSTRUCTION

Conductor: Flexible (Class 5) Annealed Plain Copper Conductor to EN 60228

Insulation: PVC (Polyvinyl Chloride) Rated at 105°C

Core Identification:
 2 Core: Blue & Brown
 3 Core: Green/Yellow, Blue & Brown
 4 Core: Green/Yellow, Black, Blue & Brown
 5 Core: Green/Yellow, Black, Blue, Brown & Black

Assembly: The cores are twisted into a round shape, with fillers incorporated as needed to maintain structural consistency.

Outer Sheath: PVC (Polyvinyl Chloride). Outer sheath colour shall be White. Other colors are available upon request.

Printing Text on the Outer Sheath (Example): TEKAB H05V2V2-F 300/500V NO. OF CORES X SIZE CU/PVC/PVC HR 105 DEG C GEN TO BS EN 50525-2-11 MADE IN UAE

TECHNICAL DATA

Operating Temperature: During Normal Operation - 105°C
 During Short Circuit Condition - 160°C

Voltage Rating: 300/500V

Flame Retardant: IEC 60332-1-2 (upon request)



SERIAL NO.	TEKAB CODE	NO. OF CORES X CONDUCTOR SIZE (NO. X Sq.mm.)	NOMINAL INSULATION THICKNESS (mm)	NOMINAL OUTER SHEATH THICKNESS (mm)	APPROX. OVERALL DIA. (mm)	APPROX. WEIGHT (kg/km)
1	H05V2V2-F_105 DEG C	2C X 0.75	0.6	0.8	6.5	60
2	H05V2V2-F_105 DEG C	2C X 1	0.6	0.8	6.8	70
3	H05V2V2-F_105 DEG C	2C X 1.5	0.7	0.8	7.7	90
4	H05V2V2-F_105 DEG C	2C X 2.5	0.8	1.0	9.4	140

SERIAL NO.	TEKAB CODE	NO. OF CORES X CONDUCTOR SIZE (NO. X Sq.mm.)	NOMINAL INSULATION THICKNESS (mm)	NOMINAL OUTER SHEATH THICKNESS (mm)	APPROX. OVERALL DIA. (mm)	APPROX. WEIGHT (kg/km)
5	H05V2V2-F-105 DEG C	2C X 4	0.8	1.1	10.7	190
6	H05V2V2-F-105 DEG C	3C X 0.75	0.6	0.8	6.9	75
7	H05V2V2-F-105 DEG C	3C X 1	0.6	0.8	7.2	85
8	H05V2V2-F-105 DEG C	3C X 1.5	0.7	0.9	8.4	115
9	H05V2V2-F-105 DEG C	3C X 2.5	0.8	1.1	10.2	175
10	H05V2V2-F-105 DEG C	3C X 4	0.8	1.2	11.5	240
11	H05V2V2-F-105 DEG C	4C X 0.75	0.6	0.8	7.5	90
12	H05V2V2-F-105 DEG C	4C X 1	0.6	0.9	8.1	105
13	H05V2V2-F-105 DEG C	4C X 1.5	0.7	1.0	9.3	140
14	H05V2V2-F-105 DEG C	4C X 2.5	0.8	1.1	11.1	210
15	H05V2V2-F-105 DEG C	4C X 4	0.8	1.2	12.6	295
16	H05V2V2-F-105 DEG C	5C X 0.75	0.6	0.9	8.4	110
17	H05V2V2-F-105 DEG C	5C X 1	0.6	0.9	8.8	130
18	H05V2V2-F-105 DEG C	5C X 1.5	0.7	1.1	10.4	180
19	H05V2V2-F-105 DEG C	5C X 2.5	0.8	1.2	12.4	265
20	H05V2V2-F-105 DEG C	5C X 4	0.8	1.4	14.1	355

Packing: Packing is available in Coil/Reel/Drum with meters/Yards/Feet.

