

INSTRUMENTATION CABLES AS PER BS EN 50288-7 (CU/LSZH/OS/LSZH)

APPLICATION

Suitable for Industrial & Commercial settings for process controls, transmission of analogue / digital signals in instrument & control systems. Ideal for use in conduits, trunking, and in locations protected from physical damage. For installation where fire, smoke emission and toxic fumes create a potential threat to life and equipment.

CONSTRUCTION

Conductor:	Stranded (Class 2) Annealed Plain Copper Conductor to BS EN 60228
Insulation:	Halogen free flame retardant compound (HFFR=LSZH)
Insulation Color:	Single Pair: Black & White Multi Pair: Black & White with number printed on each cores. Other colors are available upon request or as per BS EN 50288-7.
Pair / Triad:	Uniformly twisted insulated conductors with suitable twists per meter.
Assembly:	The required number of unscreened pairs / triads are assembled together with non-hygroscopic fillers (if required) and wrapped with a binder tape.
Overall Screen & Drain Wire:	Aluminum backed Mylar tape (25µm) (AL-PET-Foil) is applied over assembly with 100% coverage and an overlap of 25% with metal side in contact with a stranded tinned copper drain wire of size 0.5 mm ² (class 2).
Outer Sheath:	Extruded Low Smoke Zero Halogen (LSZH) in Black colour. Other colors are available upon request.
Printing Text on the Outer Sheath:	INSTRUMENTATION CABLE CU/LSZH/OS/LSZH NO OF PAIRS / TRIADS X 2 / 3 X...MM ² 500 V BS EN 50288-7 TEKAB YEAR MADE IN UAE LENGTH METER MARKING



TECHNICAL DATA

Operating Temperature:	During Normal Operation - 90°C During Short Circuit Condition - 250°C
Voltage Rating:	500V
Voltage Withstand:	2000 V a.c. r.m.s. for 1 minutes
Insulation Resistance MΩ/km:	≥ 10
Mutual Capacitance nf/km:	< 150
Inductance to resistance ratio (L/R) µH/Ω	< 25 (up to 1mm ²) < 40 (1.5 mm ²) < 60 (2.5 mm ²)

Halogen Acid Gas Emission: 0.5% (BS EN 60754-1)

Smoke Emission: 60% (BS EN 61034-2)

Flame Retardant Test: IEC 60332-3-24 (CAT C), IEC 60332-1-2

* Solid (Class-1) / Flexible (Class-5), Tinned / Thermocouple conductor can be provided upon request.

*** Screening: - Copper Tape / CU-PET tape / Braiding & any other drain wire size can be provided upon request.

**** Other special sheath materials are also available with Flame Retardant: - IEC 60332-3-22 (CAT A), UV / Sunlight Resistant, Oil Resistant, Anti-Termite, Anti-Rodent.

- Construction in core formation also can be provided upon request.
- 300V or any customized voltage grade rated cables up to 600/1000V can be provided upon request.

SERIAL NO.	TEKAB CODE	NO. OF PAIRS (P) / TRIADS (T) X CONDUCTOR SIZE (No. x sq.mm)	NO. OF STRANDS	MINIMUM INSULATION THICKNESS (mm)	APPROX. OVERALL DIAMETER (mm)	APPROX. WEIGHT (kg/km)
1	Z1A7Z1	1P X 0.5	7	0.44	6.0	50
2	Z1A7Z1	2P X 0.5	7	0.44	9.0	80
3	Z1A7Z1	5P X 0.5	7	0.44	11.5	140
4	Z1A7Z1	10P X 0.5	7	0.44	15.0	250
5	Z1A7Z1	12P X 0.5	7	0.44	16.0	285
6	Z1A7Z1	16P X 0.5	7	0.44	18.0	350
7	Z1A7Z1	20P X 0.5	7	0.44	20.0	450
8	Z1A7Z1	1P X 0.75	7	0.44	6.5	60
9	Z1A7Z1	2P X 0.75	7	0.44	10.0	110
10	Z1A7Z1	5P X 0.75	7	0.44	12.5	200
11	Z1A7Z1	10P X 0.75	7	0.44	16.5	325
12	Z1A7Z1	12P X 0.75	7	0.44	17.5	385
13	Z1A7Z1	16P X 0.75	7	0.44	20.0	500
14	Z1A7Z1	20P X 0.75	7	0.44	22.5	625
15	Z1A7Z1	1P X 1.0	7	0.44	7.0	65
16	Z1A7Z1	2P X 1.0	7	0.44	10.5	125
17	Z1A7Z1	5P X 1.0	7	0.44	13.5	225
18	Z1A7Z1	10P X 1.0	7	0.44	17.5	400
19	Z1A7Z1	12P X 1.0	7	0.44	19.0	475
20	Z1A7Z1	16P X 1.0	7	0.44	21.5	600
21	Z1A7Z1	20P X 1.0	7	0.44	24.0	750
22	Z1A7Z1	1P X 1.5	7	0.44	7.5	75
23	Z1A7Z1	2P X 1.5	7	0.44	11.5	150
24	Z1A7Z1	5P X 1.5	7	0.44	14.5	275

SERIAL NO.	TEKAB CODE	NO. OF PAIRS (P) / TRIADS (T) X CONDUCTOR SIZE (No. x sq.mm)	NO. OF STRANDS	MINIMUM INSULATION THICKNESS (mm)	APPROX. OVERALL DIAMETER (mm)	APPROX. WEIGHT (kg/km)
25	Z1A7Z1	10P X 1.5	7	0.44	19.0	500
26	Z1A7Z1	12P X 1.5	7	0.44	20.5	600
27	Z1A7Z1	16P X 1.5	7	0.44	23.5	775
28	Z1A7Z1	20P X 1.5	7	0.44	26.5	950
29	Z1A7Z1	1P X 2.5	7	0.53	8.5	110
30	Z1A7Z1	2P X 2.5	7	0.53	13.5	200
31	Z1A7Z1	5P X 2.5	7	0.53	18.0	425
32	Z1A7Z1	10P X 2.5	7	0.53	23.5	775
33	Z1A7Z1	12P X 2.5	7	0.53	25.5	900
34	Z1A7Z1	16P X 2.5	7	0.53	29.0	1175
35	Z1A7Z1	20P X 2.5	7	0.53	32.5	1475
36	Z1A7Z1	1T X 0.5	7	0.44	6.5	60
37	Z1A7Z1	2T X 0.5	7	0.44	9.5	100
38	Z1A7Z1	5T X 0.5	7	0.44	12.0	185
39	Z1A7Z1	10T X 0.5	7	0.44	15.5	325
40	Z1A7Z1	12T X 0.5	7	0.44	17.0	375
41	Z1A7Z1	16T X 0.5	7	0.44	19.5	500
42	Z1A7Z1	20T X 0.5	7	0.44	21.5	600
43	Z1A7Z1	1T X 0.75	7	0.44	7.0	75
44	Z1A7Z1	2T X 0.75	7	0.44	10.5	125
45	Z1A7Z1	5T X 0.75	7	0.44	13.5	250
46	Z1A7Z1	10T X 0.75	7	0.44	17.5	450
47	Z1A7Z1	12T X 0.75	7	0.44	19.0	525
48	Z1A7Z1	16T X 0.75	7	0.44	22.0	700
49	Z1A7Z1	20T X 0.75	7	0.44	24.0	850
50	Z1A7Z1	1T X 1.0	7	0.44	7.0	85
51	Z1A7Z1	2T X 1.0	7	0.44	11.0	150
52	Z1A7Z1	5T X 1.0	7	0.44	14.5	300
53	Z1A7Z1	10T X 1.0	7	0.44	19.0	550
54	Z1A7Z1	12T X 1.0	7	0.44	20.5	650
55	Z1A7Z1	16T X 1.0	7	0.44	23.0	850
56	Z1A7Z1	20T X 1.0	7	0.44	26.0	1050
57	Z1A7Z1	1T X 1.5	7	0.44	8.0	100
58	Z1A7Z1	2T X 1.5	7	0.44	12.0	190

SERIAL NO.	TEKAB CODE	NO. OF PAIRS (P) / TRIADS (T) X CONDUCTOR SIZE (No. x sq.mm)	NO. OF STRANDS	MINIMUM INSULATION THICKNESS (mm)	APPROX. OVERALL DIAMETER (mm)	APPROX. WEIGHT (kg/km)
59	Z1A7Z1	5T X 1.5	7	0.44	16.0	385
60	Z1A7Z1	10T X 1.5	7	0.44	20.5	700
61	Z1A7Z1	12T X 1.5	7	0.44	22.5	850
62	Z1A7Z1	16T X 1.5	7	0.44	25.5	1100
63	Z1A7Z1	20T X 1.5	7	0.44	28.5	1350
64	Z1A7Z1	1T X 2.5	7	0.53	9.5	150
65	Z1A7Z1	2T X 2.5	7	0.53	14.5	275
66	Z1A7Z1	5T X 2.5	7	0.53	19.0	575
67	Z1A7Z1	10T X 2.5	7	0.53	25.5	1100
68	Z1A7Z1	12T X 2.5	7	0.53	27.5	1300
69	Z1A7Z1	16T X 2.5	7	0.53	31.5	1700
70	Z1A7Z1	20T X 2.5	7	0.53	35.0	2100

